2020 NEW TYPE ELECTRIC TRUCK	SINGLE CABIN TYPE	DOUBLE CABIN TYPE
ELECTRIC TRUCK MODEL	72V 4KW	72V 4KW
Length-width-height (mm)	3475×1375×1550	3655X1340X1560
Inner dimension of cargo box	1620X1245X300	900X1315X400
Wheelbase (mm)	2315	2495
Front wheel base (mm)	1195	1195
Rear wheel base (mm)	1185	1185
Front overhang (mm)	455	455
Rear overhang (mm)	705	705
Weight including battery (kg)	710	835
Rated load weight (kg)	500kg	500kg
Seats	2	4
PERFORMANCE PARAMETERS		
Maximum speed (km/h)	40 (speed indicator 45)	40 (speed indicator 45)
Acceleration time s (0-40km)	15	15
Maximum climbing Angle	25%	25%
Maximum climbing angle	≤9	≤9
Minimum turning diameter(m)	36.3(outer wheel) /42(inner	36.3(outer wheel) /42(inner wheel)
Approach angle (°)	≥55	≥55
Departure angle (°)	≥35	≥30
Minimum ground clearance(mm)	≥150	≥150
BODY STRUCTURE		
Cab upper body	All sheet metal	All sheet metal
Cargo box	Three open crate	Rear open crate
BATTERY/MOTOR PARAMETERS		
Power battery specification(V/Ah)	72V / 100Ah	72V / 100Ah
Driving range(km)	120	120
The battery type	Maintenance-free lead-acid battery	Maintenance-free lead-acid battery
battery charger	220V vehicular	220V vehicular
Charging time (h)	8~10	8~10
100 kilometers of electricity (kwh)	6.5	6.5
The motor type	AC asynchronous motor	AC asynchronous motor

Motor controller	with CAN4KW	with CAN4KW
Rated power (kW)	4KW	4KW
CHASSIS/WHEEL BRAKING		
Drive form	Rear drive	Rear drive
	Double transverse arm screw spring	Double transverse arm screw spring
Front suspension type	independent suspension	independent suspension
Rear suspension type	parallel leaf spring(5PCS)	parallel leaf spring(3PCS)
Drive axle	Integral style (speed ratio 12.76)	Integral style (speed ratio 12.76)
front brake	Disc	Disc
Rear brake	Drum	Drum
Wheel	12X4B (Steel wheel4X114.3)	13x4.5B(Aluminum wheel4X114.3)
Tire size	145 R12LT	155/65 R13
Turn structure	gear rack	gear rack
power-assisted steering	-	•
Brake booster	•	•
INSIDE/OUTSIDE CONFIGURATIO	ON .	
Wiper Blade	• (long)	• (long)
Steering wheel	new type	new typw
Spray system	•	•
Machine cover	Support bar	Support bar
Lock	manual	electric
Window	manual	electric
Radio /USB player	-	-
On-board screen	•	•
USB take electricity	•	front●/rear●
Discharge port of cigarette lighter	•	front●/rear●
Combination switch	•	•
Seats	Master/deputy independent seat	Four - way adjustable, with headrest, with map bag
Rear seat	-	Strip seat, collapsible
Sun shield	main∙/vice∙	main∙/vice∙
Ceiling interior panel	•	•
Roof rails	• (1)	• (3)
Fan heater	•	•
Air conditioning	-	-
Reversing radar	-	-
Inside rear-view mirror	•	•
Head lamp	Integrated on the visor	Integrated on the visor
Instrument type	Liquid crystal digital instrument	Liquid crystal digital instrument
Headlight type	LED	LED
Rear light type	LED	LED

Rear registration plate lamp	•	-
Safety belt	main●/vice● (three point)	front● (three point) /rear-
Mud film	•	•
Forward engine compartment stora	• (small)	• (small)
Reversing camera	•	•
Axle Cover	•	•
Hubcap	-	-
Right hand drive	-	-
luggage carrier	-	-
Cargo box cover	-	-
Child safety lock	-	•
Central channel	-	•
Mobile phone holder	•	•
Front protect bar	(Front baffle with notch)	o (Front baffle with notch)
Tail mark	•	•
Roll cage	-	-
ECO	-	-
DCDC	segregate	segregate
Instrument type	72V Euro instrument	72V Euro instrument
110V battery charger	0	0